

THE FD8100 DOOR



Specifications:

Maximum Size	32' x 10', 40' x 9'
AAMA/NWWDA170	101/I.S.2.-A440-05
ASTM	1886-1996 MD201202203
Muntin	Flat
Grid Options	Colonial, Prairie, Perimeter
Product Rating	C110
HVHZ Approval	Yes
Frame Colors	White, Bronze

Frame/Track Sizes:

	Head	Jamb	Sill
2D2T w/ screen:	6 ³ / ₈ "	6 ¹ / ₄ "	7 ¹ / ₁₆ "
2D2T no screen:	5 ³ / ₁₆ "	5 ¹ / ₁₆ "	5 ¹³ / ₁₆ "
2D2T retro	5 ³ / ₁₆ "	5 ¹ / ₁₆ "	5 ³ / ₁₆ "
3D3T with screen	8 ⁷ / ₈ "	8 ⁵ / ₈ "	9 ¹ / ₂ "
3D3T no screen	7 ¹ / ₁₆ "	7 ¹ / ₂ "	8 ³ / ₈ "
4D4T no screen:	10 ³ / ₁₆ "	9 ¹⁵ / ₁₆ "	10 ¹³ / ₁₆ "

Riser for Track:

Standard:	1 ³ / ₄ "
Add-On: 1"	2 ³ / ₄ "
Add-On: 2 ³ / ₁₆ "	3 ¹⁵ / ₁₆ "

Glass Thickness:

¹ / ₄ " Tempered	¹ / ₂ " Impact	⁹ / ₁₆ " Impact
1" Insulated	1 ¹ / ₁₆ " Insulated Impact	

(Must Specify Standard or Reverse System)

Standard Items Included:

- Dual Mortise Lock w/Anti-Slam Device
- Stainless steel duel tandem Rollers with Precision Ground Bearings
- Adjustable Dual Cams on Lock
- Weep Holes in Track
- 2-point Locking System
- Anodized Track Pan w/ Snap on Cover
- Snap on jamb Covers
- 4" Sill on Panel

Extra Items Available:

- Secondary Lock (Standard on 8' or taller panels)
- 8" Panel Sill
- Colonial Muntins
- Anodized Track Cap (available only with 0 panels)
- 2 Piece Screen Adapter (Available only with OXO & OXXO systems)
- Available in 90° or 135° configurations

The most versatile impact sliding glass door for most residential & commercial installations

