


Square Aluminum Tube

6063-T52 x 24' (Unless noted otherwise)

Items marked as MILL ORDER are non stock but available. Product codes listed on MILL ORDER items are for die reference only. Customer must specify length, alloy & temper.



<u>Stock Code</u>	<u>Size in Inches (E x M x S)</u>	<u>Approx. Wt/Lin ft.</u>	<u>Stock Code</u>	<u>Size in Inches (E x M x S)</u>	<u>Approx. Wt/Lin ft.</u>
19-63-100	.500 x .062 x 20'	0.131	19-63-208	2 x .125 (w/.25 Out Rad - .125 In Rad)	1.076
19-63-471	.625 x .062 x 20'	0.168	19-63-209	2 x .125 (w/.125 radius)	1.109
19-63-095	.735 x .045	0.145	52-61-1768 (NC/DE)	2 x .125 x 32' (6005-T5) (w/.125 rad)	1.109
19-63-085	.750 x .040 (w/ .093 radius)	0.131	25-BD-315	2 x .125 x 20' (Polished BDA - w/radius)	1.109
19-63-089	.750 x .045 x 16' 8" (w/radius)	0.146	30-05-200 (NC/DE) #	2 x .125 x 32' (Ribbed Dock Tube, w/rad)	0.994
19-63-101	.750 x .045 x 18' 8" (w/radius)	0.146	19-61-208	2 x .188 (6061-T6)	1.634
19-63-525 (NC)	.750 x .062 x 16'	0.206	19-63-211	2 x .188	1.627
19-63-106 (TX)	.750 x .062 x 20'	0.206	52-61-1128	2 x .188 x 20' (w/.406 radius/6061-T6)	1.530
19-63-638 (NC)	.750 x .062 x 21' (w/radius)	0.196	19-61-212	2 x .250 (6061-T6)	2.100
19-63-106 (MO)	.750 x .062 x 21' (w/radius)	0.196	52-61-1520	2 x .250 (6061-T6 - w/.250 rad)	2.052
19-63-108 (MO)	.750 x .062 x 22' (w/radius)	0.196	19-63-215	2.250 x .095	0.982
19-63-105	.750 x .062	0.206	52-61-1040	2.45 x .250 x 18' (w/radius/6061-T6)	2.640
19-63-107	.750 x .062 (w/.090 radius)	0.206	19-63-714	2.500 x .075	0.855
19-63-110	.750 x .093	0.293	19-63-807 (DE)	2.500 x .093	1.074
19-63-113	.750 x .093 (w/radius)	0.293	19-63-221	2.500 x .125	1.425
19-63-115	.750 x 1/8	0.374	MILL ORDER	2.500 x .188 (6063-T6) 52-61-3402	2.076
19-63-116	.750 x 1/8 (.062 radius)	0.374	28-60-730	2.5 x .375 x 24' (6005A-T61)	3.824
19-63-821 (DE)	1 x .047	0.214	52-61-4450	2.7 x .125 (w/radius/6061-T6)	1.490
19-63-130	1 x .062	0.278	19-61-534 (NC/MO/DE/AL)	2.7 x .125 x 20' (w/radius/6061-T6)	1.490
19-63-131	1 x .062 (w/radius)	0.268	19-63-230	3 x .093	1.298
19-63-136 (NC/MO)	1 x .075 (w/radius)	0.317	19-63-231	3 x .093 x 27'	1.298
19-63-341	1 x .093	0.405	MILL ORDER	3 x .100 (T5 w/rad) 242-005 (MO)	1.380
19-63-345	1 x .093 (w/radius)	0.392	19-63-235	3 x .125	1.726
19-63-140	1 x .125	0.524	19-61-535 (NC/TX/MO)	3 x .125 x 20' (w/rad/6061-T6)	1.670
19-61-140	1 x .125 (6061-T6)	0.524	19-63-237	3 x .125 (w/.125 radius)	1.774
19-63-141	1 x .125 (w/radius)	0.509	30-05-205 (NC/DE) #	3 x .125 x 20' (Ribbed Dock Tube, w/rad)	1.546
25-BD-310	1 x .125 x 20' Polished BDA (w/rad)	0.509	52-61-749	3 x .188 x 18' (w/radius 6061-T6)	2.502
19-63-153	1.250 x .062	0.353	52-63-8188	3 x .188 x 25' (w/radius 6063-T6)	2.502
19-63-150	1.250 x .093	0.516	19-63-240	3 x .188	2.533
19-61-150	1.250 x .093 (6061-T6)	0.516	19-61-340	3 x .250 (6061-T6)	3.300
19-63-152	1.250 x .093 (w/ .062 radius)	0.506	51-63-897	3 x .250 x 18' 3" (w/rad)	3.204
19-63-155	1.250 x .125	0.675	52-63-8441	3 x .250 x 25' (w/radius 6063-T6)	3.204
19-63-157	1.250 x .125 x 20' (w/radius)	0.643	52-61-750	3 x .250 x 18' (w/radius 6061-T6)	3.204
19-63-160	1.500 x .060	0.430	28-60-765	3.5 x .230 x 24' (6005A-T61)	3.610
19-63-161	1.500 x .062 (w/ .093 radius)	0.420	19-63-245	4 x .125	2.324
19-63-168	1.500 x .090 (.188 radius)	0.582	56-63-003	4 x .125 x 24' 2" (w/radius 204R1 Anod)	2.374
19-63-165	1.500 x .093	0.632	56-63-010	4 x .150 x 22' (w/radius 204R1 Anod)	2.772
19-61-165	1.500 x .093 (6061-T6)	0.632	MILL ORDER	4 x .156 (w/rad; 4 screw bosses) 21929-997 (TX)	4.282
19-63-170	1.500 x .125	0.824	19-61-250	4 x .250 (6061-T6)	4.500
19-61-170	1.500 x .125 (6061-T6)	0.824	56-MF-035	4.5 x .093 (w/.125 radius)	1.955
19-63-172	1.500 x .125 (w/.125 radius)	0.809	19-63-255	5 x .125	2.925
19-63-174	1.500 x .188	1.184	19-61-258	5 x .250 (6061-T6)	5.700
19-61-173	1.500 x .250 (6061-T6)	1.500	MILL ORDER	5.5 x .204 (T6 w/radius) 19-63-721 (NC)	5.173
52-61-1045	1.500 x .250 x 18' (w/rad/6061-T6)	1.461	19-63-260	6 x .125	3.525
19-63-180	1.750 x .093	0.732	56-63-037	6 x .150 x 24' 6" (6063-T6 w/rad 204R1 Anod)	4.204
19-61-180	1.750 x .093 (6061-T6)	0.732	MILL ORDER	6 x .180 x 20' (w/rad) 52-63-1843	5.076
19-63-185	1.750 x .125	0.975	MILL ORDER	6 x .180 (w/rad; 4 screw bosses) 21929-998 (TX)	6.929
19-63-192	2 x .062	0.604	MILL ORDER	6 x .188 (w/rad, 6063-T6) 52-63-12856	5.245
19-63-191	2 x .062 x 26'	0.604	19-61-260	6 x .25	6.900
19-61-206	2 x .093 (6005 T5)	0.851	19-61-261	6 x .50 (6061-T6)	12.936
19-61-205	2 x .093 x 26' (6005-T5)	0.851	MILL ORDER	6.75 x .188	5.804
52-61-11425	2 x .093 (w/radius 6061-T6)	0.836	19-63-262	7 x .156 (6063-T6)	5.120
19-63-210	2 x .125	1.126	19-63-265	8 x .188	7.050
52-61-936	2 x .125 (6061-T6)	1.126	MILL ORDER	8 x .50 (6061-T6 w/rad) 52-61-3166	17.650
19-61-210	2 x .125 x 22' 6" (6061-T6)	1.126	19-63-300	10 x .250 x 24' (6063-T6 w/rad)	11.700
			52-61-2163	Post Stiffener I-Beam for 2" x .125 Sq Tube	0.976
			52-61-4452	Post Stiffener I-Beam for 2" x .188 Sq Tube	0.995
			52-61-2811	Post Stiffener I-Beam for 2.5" x .125 Sq Tube	0.961
			MILL ORDER 52-61-3403	Post Stiffener I-Beam for 2.5" x .375 Sq Tube	1.708

Standards 15



EMS FL

1-800-432-2204
(561) 588-4780 - fax

EMS NC

1-800-343-8154
(704) 391-2267 - fax

EMS TX

1-800-996-6061
(281) 656-2297 - fax

EMS MO

1-888-822-6061
(314) 344-3349 - fax

Eastern Metal Supply

Quality Shapes In Aluminum

Additional Locations: West Palm Beach & Lakeland, FL; Newark, DE; Birmingham, AL, Akron, OH and Van Buren, AR

website: www.EasternMetal.com

e-mail: info@EasternMetal.com

version: 06/11/18