














# Railing Channel

<p><b>1.5 x 1 (.093/.056) Railing Channel x 25'</b> 13-63-300 wt/ft: 0.332 6063-T5 Receives .750 picket; Mates with 13-63-305</p>  <p><b>Accepts Casting:</b> Wall Mount HR-12A #68: 21-00-183</p>	<p><b>1.75 x .75 (.093/.062) Railing Channel x 24'</b> 13-63-264 wt/ft: 0.330 6063-T5 Receives .750 picket;</p> 	<p><b>2 x 1 (.093/.056) Railing Channel x 25'</b> 13-63-266 wt/ft: 0.395 6063-T5 Receives .750 picket; Mates with 13-63-227</p> 	<p><b>2 x 1 (.090/.056) Railing Channel x 25'</b> 13-63-267 wt/ft: 0.395 6063-T5 Receives 1" picket; Mates with 13-63-227</p>  <p><b>Accepts Casting:</b> Wall Mount #15: 21-00-190</p>
<p><b>1.5" Railing Channel Cover Plate x 20'</b> 13-63-305 wt/ft: 0.146 6063-T5 Mates with 13-63-300</p> 	<p><b>2" Railing Channel Cover Plate x 16'</b> 13-63-227 wt/ft: 0.175 6063-T5 Mates with 13-63-266 &amp; 13-63-267</p> 	<p><b>2 x 7/16 x .093 Railing Channel x 25' 2"</b> 13-63-261 wt/ft: 0.294 6063-T5 No Legs</p> 	<p><b>2 x .75 (.125/.093) Railing Channel x 23' 10"</b> 13-63-262 wt/ft: 0.440 6063-T5 No Legs</p> 
<p><b>2 x 1 x .125 Channel x 20'</b> 13-63-265 <b>13-63-274</b> x 24' wt/ft: 0.563 6063-T5</p> 	<p><b>2 x 1 Mid Rail Tube x 24'</b> 52-63-11317 wt/ft: 0.858 6063-T52</p>  <p><b>Accepts Casting:</b> Wall Mount #15: 21-00-190</p>	<p><b>2.252 x 1.280 Outside Sleeve x 12'</b> 52-63-4808 wt/ft: 0.562 6063-T6 Sleeves 2 x 1 Channel and Rectangular Tube</p> 	<p><b>2 x 2 x .125 Channel x 20'</b> 13-63-272 wt/ft: 0.861 6063-T5</p> 


## Pre-Punched Arch Aluminum Railing Channel (Mill Finish 6063-T5)

Stock Code	Size in Inches	Picket
13-63-265P	2 x 1 x .125 x 20'	3/4"
13-63-266P*	2 x 1 x .093/.056 x 25'	3/4"
13-63-26620P*	2 x 1 x .093/.056 x 20'	3/4"
13-63-265PR**	2 x 1 x .125 x 24'	3/4"
13-63-266PR**	2 x 1 x .093/.056 x 25'	3/4"
13-63-274PP	2 x 1 x .125 x 24'	1"
13-63-274PPR**	2 x 1 x .125 x 24'	1"
13-63-26720P*	2 x 1 x .093/.056 x 20'	1"
13-63-267P*	2 x 1 x .093/.056 x 25'	1"

\*with welding legs \*\*for pickets with radius corners




3.75" spacing between holes inside edge to inside edge



## Picket Spears

19-63-105PS1	3/4 x .062 x 58"
19-63-105PS2	3/4 x .062 x 70"
19-63-130PS1	1 x .060 x 58"
19-63-130PS2	1 x .060 x 70"

3/4" & 1" Spears



3.75 Decorative Aluminum Rings Casting  
21-00-377

Custom sizes and hole locations available as **SPECIAL ORDER**

Mill Order Items: Not in Stock - Custom Sizes & Lengths Available Minimum Order Required

RAILING & FENCE 08



**Eastern Metal Supply** www.easternmetal.com • info@easternmetal.com 06/30/20  
FL: 800-432-2204 • NC/DE/GA: 800-343-8154 • TX/AR: 800-996-6061 • MO/OH: 888-822-6061

**1" Picket - HR-5**  
**200-WH-075** White x 19'10"  
**200-MB-075** Bronze x 19'10"  
**HR-5-WH** White x 23'  
**HR-5-BR** Bronze x 23'  
**HR-5-BK** Black x 23' 6"  
**HR-5-MF** (TX) Mill Finish x 23'  
 20 pc sub-bundles

**1" Oval Picket**  
**MILL ORDER - 52-63-12344**

**3/4" Picket - HR-13**  
**HR-13-WH-1** White x 19' 1"  
**HR-13-BR-1** Bronze x 19' 1"  
**HR-13-BK** Black x 19' 1"  
**HR-13-WH** White x 22' 5"  
**HR-13-BR** Bronze x 22' 5"  
 20 pc sub-bundles

**3/4" Picket w/radius**  
**HR-13R (.120 Radius)**  
**HR-13R-WH20** White x 20'  
**HR-13R-BR20** Bronze x 20'  
**HR-13R-WH (MO)** White x 24'  
**HR-13R-BR (MO)** Bronze x 24'  
 20 pc sub-bundles

**3/4" Spears**  
**19-63-105PS1** .062 x 58"  
**19-63-105PS2** .062 x 70"

**1" Spears**  
**19-63-130PS1** .060 x 58"  
**19-63-130PS2** .062 x 70"

### Aluminum Posts & Pickets

#### Painted Square Tube - 6063-T6

Stock Code	Size in Inches	Approx. Wt/Lin ft.
19-WH-204	2 x .093 x 24' White	0.851
19-MB-204	2 x .093 x 24' Bronze	0.851
19-BK-204	2 x .093 x 24' Black	0.851
19-IV-300	2 x .125 x 24' Ivory	1.125
19-WH-305	2 x .125 x 24' 6" White	1.125
19-MB-305	2 x .125 x 24' 6" Bronze	1.125
19-BG-305	2 x .125 x 24' 6" Beige	1.125
19-COLOR-212	2 x .250 x 24' **	2.100
19-WH-003	3 x .093 x 24' White	1.298
19-MB-003	3 x .093 x 24' Bronze	1.298
200-WH-027	3 x .093 x 30' White	1.298
200-MB-027	3 x .093 x 30' Bronze	1.298
19-WH-225	3 x .125 x 20' White	1.726
19-WH-220	3 x .125 x 24' White	1.726
19-MB-235	3 x .125 x 24' Bronze	1.726
19-IV-235	3 x .125 x 24' Ivory	1.726
19-BG-235	3 x .125 x 24' Beige	1.726
19-BK-235	3 x .125 x 24' Black	1.726
19-COLOR-240	3 x .250 x 24' **	3.300
52-COLOR-4424	3.50 x .125 x 24' **	2.024
19-WH-245	4 x .125 x 20' White	2.325
19-WH-400	4 x .125 x 24' White	2.325
19-MB-246	4 x .125 x 24' Bronze	2.325
19-IV-400	4 x .125 x 24' Ivory	2.325
19-BG-400	4 x .125 x 24' Beige	2.325
19-BK-400	4 x .125 x 24' Black	2.325
200-WH-028	4 x .125 x 30' White	2.325
200-MB-028	4 x .125 x 30' Bronze	2.325
19-WH-2500	4 x .250 x 20' White	4.500
19-MB-2500	4 x .250 x 24' Bronze	4.500
19-IV-2500	4 x .250 x 24' Ivory	4.500
19-BG-2500	4 x .250 x 24' Beige	4.500
19-WH-2501	4 x .250 x 24' 6" White	4.500

#### 3" Scalloped Square Tube

42-WH-003 (MO)	3" x 20' White	0.757
200-WH-017	3" x 24' White	0.757
200-MB-017	3" x 24' Bronze	0.757
200-WH-018	3" x 30' White	0.757
200-MB-018	3" x 30' Bronze	0.757

\*\*COLOR - Available in White (WH), Bronze (MB), Ivory (IV), and Beige (BG)

### Aluminum Woven Wire Mesh - NEW!

Alloy 1350 - H16

ID Size	Stock Code	Size in Inches	Approx. Wt/Sheet
1.75 ID	50-WWM-4896	.236 x 48 x 96	21.12
1.75 ID	50-WWM-48120	.236 x 48 x 120	26.40
2.00 ID	50-2X2WM-4896	.236 x 48 x 96	17.60
2.00 ID	50-2X2WM-48120	.236 x 48 x 120	21.78

#### Woven Wire Mesh Framing Options

see *Stiffeners, Enclosures & Gates 11 for schematic*

13-63-205	1/2 x 3/4 x 1/8 Channel x 20' (6063-T52)
60-00-205	MP-1A (1 x 1 x 24')
59-63-002 (TX)	MP-1A (1 x 1 x 24')

**Hard-Rok**  
**61-00-007** 5 Gallon Bucket  
 Contains no gypsum or chlorides;  
 Quick setting anchoring cement;

**Quik Rok**  
**61-00-001** 5 Gallon Bucket  
 Anchoring Cement  
 NEVER to be used to anchor balcony railing or any similar human life safety structures

**45° Post x 20'** #2  
**52-63-2033** wt/ft: 1.041  
 Wall: .085/.150 6061-T6

**16 oz Touch Up Spray Paint**

Stock Code	Color
35-00-100	White
35-00-100G	White Gloss
35-00-105	Bronze
35-00-105G	Bronze Gloss
35-00-110	Ivory Gloss
35-00-115 (TX)	Beige
35-00-115G	Beige Gloss
35-00-120	Black
35-00-120G	Black Gloss

**RAILING & FENCE 03**

# Square Aluminum Tube



## 6063-T52 x 24' (Unless noted otherwise)

Stock Code	Size in Inches (E x M x S)	Approx. Wt/Lin ft.	Stock Code	Size in Inches (E x M x S)	Approx. Wt/Lin ft.
19-63-100	.500 x .062 x 20'	0.131	19-63-209	2 x .125 (w/.125 radius)	1.109
19-63-471	.625 x .062 x 20'	0.168	52-61-1768 (NC/DE)	2 x .125 x 32' (6005-T5) (w/.125 rad)	1.109
19-63-095	.735 x .045	0.145	25-BD-315	2 x .125 x 20' (Polished BDA - w/radius)	1.109
19-63-085	.750 x .040 (w/ .093 radius)	0.131	30-05-200 (NC/DE) #	2 x .125 x 32' (Ribbed Dock Tube, w/rad)	0.994
19-63-089	.750 x .045 x 16' 8" (w/radius)	0.146	19-61-208	2 x .188 (6061-T6)	1.634
19-63-101	.750 x .045 x 18' 8" (w/radius)	0.146	19-63-211	2 x .188	1.627
19-63-525 (NC)	.750 x .062 x 16'	0.206	52-61-1128	2 x .188 x 20' (w/.406 radius/6061-T6)	1.530
19-63-638 (NC)	.750 x .062 x 21' (w/radius)	0.196	19-61-212	2 x .250 (6061-T6)	2.100
19-63-106 (MO)	.750 x .062 x 21' (w/radius)	0.196	52-61-1520	2 x .250 (6061-T6 - w/.250 rad)	2.052
19-63-108 (MO)	.750 x .062 x 22' (w/radius)	0.196	19-63-215	2.250 x .095	0.982
19-63-105	.750 x .062	0.206	52-61-1040	2.45 x .250 x 18' (w/radius/6061-T6)	2.640
19-63-107	.750 x .062 (w/.090 radius)	0.206	19-63-714	2.500 x .075	0.855
19-63-110	.750 x .093	0.293	19-63-807 (DE)	2.500 x .093	1.074
19-63-113	.750 x .093 (w/radius)	0.293	19-63-221	2.500 x .125	1.425
19-63-115	.750 x 1/8	0.374	28-60-735	2.500 x .125/.375 (6005A-T61)	2.774
19-63-116	.750 x 1/8 (.062 radius)	0.374	MILL ORDER	2.500 x .188 <u>52-61-3402</u>	2.076
19-63-821 (DE)	1 x .047	0.214	28-60-730	2.5 x .375 (6005A-T61)	3.824
19-63-130	1 x .062	0.278	52-61-4450	2.69 x .125 (w/.250 radius/6061-T6)	1.490
19-63-131 (NC/MO/TX)	1 x .062 (w/radius)	0.268	19-61-534 (NC/MO/DEAL)	2.69 x .125 x 20' (w/.250 radius/6061-T6)	1.490
19-63-131 (FL)	1 x .062 (w/radius - 6060-T6)	0.268	19-63-230	3 x .093	1.298
19-63-136 (NC/MO)	1 x .075 (w/radius)	0.317	19-63-231	3 x .093 x 27'	1.298
19-63-341	1 x .093	0.405	19-63-235	3 x .125	1.726
19-63-345	1 x .093 (w/radius)	0.392	19-61-535 (NC/TX/MO)	3 x .125 x 20' (w/rad/6061-T6)	1.670
19-63-140	1 x .125	0.524	19-63-237	3 x .125 (w/.125 radius)	1.774
19-61-140	1 x .125 (6061-T6)	0.524	30-05-205 (NC/DE) #	3 x .125 x 20' (Ribbed Dock Tube, w/rad)	1.546
19-63-141	1 x .125 (w/radius)	0.509	52-61-749	3 x .188 x 18' (w/radius 6061-T6)	2.502
25-BD-310	1 x .125 x 20' Polished BDA (w/rad)	0.509	52-63-8188	3 x .188 x 25' (w/radius 6063-T6)	2.502
19-63-153	1.250 x .062	0.353	19-63-240	3 x .188	2.533
19-63-150	1.250 x .093	0.516	19-61-340	3 x .250 (6061-T6)	3.300
19-61-150	1.250 x .093 (6061-T6)	0.516	51-63-897	3 x .250 x 18' 3" (w/rad)	3.204
19-63-152	1.250 x .093 (w/ .062 radius)	0.506	52-63-8441	3 x .250 x 25' (w/radius 6063-T6)	3.204
19-63-155	1.250 x .125	0.675	52-61-750	3 x .250 x 18' (w/radius 6061-T6)	3.204
19-63-157	1.250 x .125 x 20' (w/radius)	0.643	28-60-765	3.5 x .230 (6005A-T61)	3.610
19-63-160	1.500 x .060	0.430	19-63-245	4 x .125	2.324
19-63-161	1.500 x .062 (w/ .093 radius)	0.420	56-MF-003	4 x .125 x 24' 2" (w/radius 6063-T6 MF)	2.374
19-63-168	1.500 x .090 (.188 radius)	0.582	56-63-003	4 x .125 x 24' 2" (w/radius 204R1 Anod)	2.374
19-63-165	1.500 x .090	0.632	56-MF-010	4 x .150 x 22' (w/radius 6063-T6 MF)	2.772
19-61-165	1.500 x .090 (6061-T6)	0.632	56-63-010	4 x .150 x 22' (w/radius 204R1 Anod)	2.772
19-63-170	1.500 x .125	0.824	MILL ORDER	4 x .156 (w/rad; 4 screw bosses) 21929-997 (TX)	4.282
19-61-170	1.500 x .125 (6061-T6)	0.824	19-61-250	4 x .250 (6061-T6)	4.500
19-63-172	1.500 x .125 (w/.125 radius)	0.809	19-61-251	4 x .250 (w/.375 radius; 6061-T6)	4.500
19-63-174	1.500 x .188	1.184	56-MF-035	4.5 x .093 x 24' w/.125 radius 6063-T6 MF	1.955
19-61-173	1.500 x .250 (6061-T6)	1.500	19-63-255	5 x .125	2.925
52-61-1045	1.500 x .250 x 18' (w/rad/6061-T6)	1.461	19-61-258	5 x .250 (6061-T6)	5.700
19-63-180	1.750 x .093	0.732	19-63-260	6 x .125	3.525
19-61-180	1.750 x .093 (6061-T6)	0.732	56-63-037	6 x .150 x 24' 6" (6063-T6 w/rad 204R1 Anod)	4.204
19-63-185	1.750 x .125	0.975	19-63-302 (TX)	6 x .180 (w/.250 rad; 6005-T5 MF)	5.028
19-63-192	2 x .062	0.604	MILL ORDER	6 x .180 (w/rad; 4 screw bosses) 21929-998 (TX)	6.929
19-63-191	2 x .062 x 26'	0.604	19-61-260	6 x .25 (6061-T6)	6.900
19-61-206	2 x .093 (6005 T5)	0.851	19-61-261	6 x .50 (6061-T6)	12.936
19-61-205	2 x .093 x 26' (6005-T5)	0.851	19-63-262	7 x .156 (6063-T6)	5.120
52-61-11425	2 x .093 (w/radius 6061-T6)	0.836	19-63-265	8 x .188	7.050
19-63-210	2 x .125	1.126	19-61-270	8 x .250 (6061-T6)	9.114
52-61-936	2 x .125 (6061-T6)	1.126	MILL ORDER	8 x .50 <u>52-61-3166</u>	17.650
19-61-210	2 x .125 x 22' 6" (6061-T6)	1.126	19-63-300	10 x .250 (6063-T6 w/rad)	11.700
19-63-208	2 x .125 (w/.25 Out Rad - .125 In Rad)	1.076	19-63-400	12 x .250 (w/.125 rad)	13.803
			52-61-2163	Stiffener I-Beam for 2" x .125 Sq Tube 6061-T6	0.976
			52-61-4452	Stiffener I-Beam for 2" x .188 Sq Tube 6061-T6	0.995
			52-61-2811	Stiffener I-Beam for 2.5" x .125 Sq Tube 6061-T6	0.961

Items marked as MILL ORDER are non stock but available. Product codes listed on MILL ORDER items are for die reference only. Customer must specify length, alloy & temper.

### Standards 17



#### EMS FL

1-800-432-2204  
(561) 588-4780 - fax

#### EMS NC

1-800-343-8154  
(704) 391-2267 - fax

#### EMS TX

1-800-996-6061  
(281) 656-2297 - fax




#### EMS MO





1-888-822-6061  
(314) 344-3349 - fax

**Eastern Metal Supply** Additional Locations: West Palm Beach & Lakeland, FL; Newark, DE; Akron, OH, Van Buren, AR; Atlanta, GA and Dallas, TX

Quality Shapes In Aluminum [website: www.EasternMetal.com](http://www.EasternMetal.com) [e-mail: info@EasternMetal.com](mailto:info@EasternMetal.com) **version: 08/31/20**

# Pipe Brackets (See Standards 21-22 for full selection of Pipe)



	<p><b>2.25" x 3.875" Centerline Projected Pipe Bracket x 16'</b>                  31-63-135      163                  wt/ft: 1.940</p> 	<p><b>2.50" x 3.875" Centerline Projected Pipe Bracket x 16'</b>                  31-63-120      162                  wt/ft: 2.012</p> 
---	---	--

<p><b>2.875" x 3.50" Centerline Projected Pipe Bracket x 16'</b>                  31-63-105      160                  wt/ft: 1.853</p> 	<p><b>2.50" x 4.375" Centerline Projected Pipe Bracket x 16'</b>                  31-63-140      164                  wt/ft: 2.154</p> 	<p><b>3.080" x 3.875" Centerline Projected Pipe Bracket x 16'</b>                  31-61-145      165                  wt/ft: 2.1815</p> 	<p><b>3.125" x 4.375" Centerline Projected Pipe Bracket x 12'</b>                  31-61-150      wt/ft: 2.264                  Meets NFPA 101 Life Safety Code</p> 
--	--	---	---

**Grip Rail - NEW!**



<b>Polished &amp; Anodized</b>	<b>Mill Finish</b>
Stock Code	Stock Code
<b>Description</b>	<b>Description</b>
GR-12 12"	GRM-12 12"
GR-14 14"	GRM-14 14"
GR-18 18"	GRM-18 18"
GR-24 24"	GRM-24 24"
GR-36 36"	GRM-36 36"



<p><b>Mark 5 Gate Hinge*</b>  <b>52-63-8793</b>                  (Heavy Duty)                  with base plate                  *up to 800 lb load</p> 	<p><b>Mark 4 Gate Hinge</b>  <b>52-63-9150</b>                  (Heavy Duty) without base plate</p> 
---	---

**SCH 40 Aluminum Pipe End Caps**

<b>Mill Finish</b>	<b>Pipe Size</b>
APC-100-MF	1
APC-125-MF	1-1/4
APC-150-MF	1-1/2
APC-200-MF	2
<b>Anodized</b>	
APC-750	3/4
APC-100	1
APC-125	1-1/4
APC-150	1-1/2
APC-200	2
<b>Black Plastic</b>	
RN1-1/4DBK1	1



**SCH 40 Pipe x 24' - T4 Temper (for bending)**

<b>Stock Code</b>	<b>Size in Inches</b>
18-63-231	1-1/4 x 1.660 OD x 1.380 ID x .140 Wall
18-T4-500	1-1/2 x 1.900 OD x 1.610 ID x .145 Wall

**Many other Pipe sizes, Alloys & Temper are Available**

**Pipe Inserts (6063-T52)**

18-63-259	1-1/4	SCH 40 x 10'
18-63-260	1-1/2	SCH 40 x 10'
51-00-051	1-3/8	Serrated Tube x 20' (insert for 1-1/4 pipe)

# SCH 40 Aluminum Pipe - 6063-T52 x 20'

Stock Code	Size in Inches			Approx. Wt/Lin ft.
	(Size)	OD x ID x Wall		
18-63-200	1/8	.405 x .269 x .068 (12')	0.085	
18-63-205	1/4	.540 x .364 x .083 (12')	0.147	
18-63-210	3/8	.675 x .493 x .091	0.196	
18-63-215	1/2	.840 x .622 x .109	0.294	
18-63-220	3/4	1.050 x .824 x .113	0.391	
18-DOT-220*	3/4	1.050 x .824 x .113	0.391	
18-63-221	3/4	1.050 x .824 x .113 (23')	0.391	
18-63-225	1	1.315 x 1.049 x .133	0.581	
18-DOT-225*	1	1.315 x 1.049 x .133	0.581	
18-63-226	1	1.315 x 1.049 x .133 (23')	0.581	
18-63-230	1-1/4	1.660 x 1.380 x .140	0.786	
18-63-233	1-1/4	1.660 x 1.380 x .140 (23')	0.786	
18-63-232	1-1/4	1.660 x 1.380 x .140 (24')	0.786	
18-63-235	1-1/2	1.900 x 1.610 x .145	0.940	
18-DOT-235*	1-1/2	1.900 x 1.610 x .145	0.940	
18-63-236	1-1/2	1.900 x 1.610 x .145 (23')	0.940	
18-63-240	2	2-3/8 x 2.067 x .154	1.264	
18-DOT-240*	2	2-3/8 x 2.067 x .154	1.264	
18-63-241	2	2-3/8 x 2.067 x .154 (23')	1.264	
18-63-245	2-1/2	2-7/8 x 2.469 x .203	2.004	
18-63-250	3	3-1/2 x 3.068 x .216	2.621	
18-63-255	3-1/2	4 x 3.548 x .226	3.151	



\*6063-T52 Full Certs Available

## SCH 40 Aluminum Pipe - T4 Temper


MILL ORDER (40-63-603)	1-1/4	1.660 x 1.380 x .140 (10')	0.786
18-63-231	1-1/4	1.660 x 1.380 x .140 (24')	0.786
18-T4-500	1-1/2	1.900 x 1.610 x .145 (24')	0.940

## SCH 40 Aluminum Pipe - 6061-T6 x 20'


18-61-215	1/2	.840 x .622 x .109	0.294
18-61-220	3/4	1.050 x .824 x .113	0.391
18-61-222	3/4	1.050 x .824 x .113 (24')	0.391
18-61-225	1	1.315 x 1.049 x .133	0.581
18-61-230	1-1/4	1.660 x 1.380 x .140	0.786
18-61-235	1-1/2	1.900 x 1.610 x .145	0.940
18-61-240	2	2-3/8 x 2.067 x .154	1.264
18-61-241	2	2-3/8 x 2.067 x .154 (24')	1.264
18-61-243	2	2-3/8 x 2.067 x .154 (30')	1.264
18-61-245 (NC/DE)	2-1/2	2-7/8 x 2.469 x .203	2.004
18-61-246	2-1/2	2-7/8 x 2.469 x .203 (22')	2.004
18-61-250	3	3-1/2 x 3.068 x .216	2.621
18-61-255	3-1/2	4 x 3.548 x .226	3.151
18-61-260	4	4-1/2 x 4.026 x .237	3.733
18-61-265	5	5.563 x 5.047 x .258	5.057
18-61-270	6	6-5/8 x 6.065 x .280	6.564
18-61-280	8	8-5/8 x 7.981 x .322	9.878
18-61-290	10	10-3/4 x 10.020 x .365	14.288
18-61-295	12	12-3/4 x 11.938 x .406	18.893

**ALSO AVAILABLE:** Brushed or Polished BDA Pipe (Marine Section pp 01-02)


2.25" x 3.875" Centerline  
Projected Pipe Bracket x 16'  
31-63-135 163 wt/ft: 1.940




2.50" x 3.875" Centerline  
Projected Pipe Bracket x 16'  
31-63-120 162 wt/ft: 2.012




2.875" x 3.50" Centerline  
Projected Pipe Bracket x 16'  
31-63-105 160 wt/ft: 1.853




2.50" x 4.375" Centerline  
Projected Pipe Bracket x 16'  
31-63-140 164 wt/ft: 2.154




3.080" x 3.875" Centerline  
Projected Pipe Bracket x 16'  
31-61-145 165 wt/ft: 2.1815



3.125" x 4.375" Centerline  
Projected Pipe Bracket x 12'  
31-61-150 wt/ft: 2.264  
Meets NFPA 101 Life Safety Code




Pipe Inserts for SCH 40 Pipe  
18-63-259  
for 1-1/4 SCH 40 x 10' 0.492  
18-63-260  
1-1/2 SCH 40 x 10' 0.582  
52-61-3454  
for 2 SCH 40 x 20' (6061) 0.698




Elbows  
21-63-230  
1-1/4" SCH 40 Elbow  
21-63-235  
1-1/2" SCH 40 Elbow



Pipe Inserts for SCH 40 Pipe  
51-00-051 1-3/8  
Serrated Tube x 20' 0.408  
(insert for 1-1/4 pipe)



Grooved End Pipe  
Available by Mill Order  
2" SCH 40 - 10" SCH 40  
Accepts Victaulic® Couplings  
www.victaulic.com



### Standards 23



**EMS FL**  
1-800-432-2204  
(561) 588-4780 - fax

**EMS NC**  
1-800-343-8154  
(704) 391-2267 - fax


**EMS TX**  
1-800-996-6061  
(281) 656-2297 - fax

**EMS MO**  
1-888-822-6061  
(314) 344-3349 - fax

**Eastern Metal Supply** Additional Locations: West Palm Beach & Lakeland, FL; Newark, DE; Akron, OH, Van Buren, AR; Atlanta, GA and Dallas, TX  
Quality Shapes In Aluminum [website: www.EasternMetal.com](http://www.EasternMetal.com) [e-mail: info@EasternMetal.com](mailto:info@EasternMetal.com) [version: 01/22/20](http://www.victaulic.com)

# SCH 80 Aluminum Pipe - 6063-T52 x 20'

Stock Code	Size in Inches			Approx. Wt/Lin ft.
	(Size)	OD x ID x Wall		
MILL ORDER 26-63-201 (TX)	1	1.315 x .957 x .179 (T5)		0.751
<u>26-63-105</u>	1-1/4	1.660 x 1.278 x .191		1.037
26-63-100	1-1/2	1.900 x 1-1/2 x .200		1.256
26-63-200	2	2-3/8 x 1.939 x .218		1.737
MILL ORDER	3	3-1/2 x 2.900 x .300		3.547
MILL ORDER <u>52-63-8819</u>	4	4-1/2 x 3.826 x .337		5.183



**ALSO AVAILABLE:**  
**Brushed & Polished BDA Pipe**  
 See the Marine section of our Catalog

## SCH 80 Aluminum Pipe - 6061-T6 x 20'

<u>26-61-025</u>	1/4	0.540 x .287 x .119 (x 12')		0.182
26-61-200	1	1.315 x .957 x .179		0.751
26-61-205	1-1/4	1.660 x 1.278 x .191		1.037
26-61-210	1-1/2	1.900 x 1-1/2 x .200		1.256
26-61-215	2	2-3/8 x 1.939 x .218		1.737
<u>26-61-215S</u>	2	2-3/8 x 1.910 x .233		1.878
26-61-220	2-1/2	2-7/8 x 2.323 x .276		2.705
26-61-225	3	3-1/2 x 2.900 x .300		3.547
26-61-230	3-1/2	4.000 x 3.364 x .318		4.414
26-61-235	4	4-1/2 x 3.826 x .337		5.288
<u>52-61-2343</u>	5	5.563 x 4.813 x 3/8 (T6)		7.188
<u>26-61-250</u>	6	6-5/8 x 5.761 x .432 (T6)		9.884
<u>26-61-255</u>	8	8-5/8 x 7.625 x 1/2		15.010

## SCH 10 Aluminum Pipe - 6063-T52 x 20'

MILL ORDER 32-63-200 (NC)	1	1.315 x 1.097 x .109 (T6)		0.486
<u>32-63-204</u>	1-1/4	1.660 x 1.442 x .109		0.625
32-63-205	1-1/2	1.900 x 1.682 x .109		0.721
<u>32-63-205S</u>	1-1/2	1.902 x 1.702 x .100 (Special ID)		0.679
MILL ORDER <u>52-63-10742</u>	2	2-3/8 x 2.157 x .109 (T5)		0.913
<u>DOT-61-170</u> (6061-T6)	2-1/2	2-7/8 x 2.635 x .120 x 24' (6061-T6)		1.221
MILL ORDER 32-63-220 (NC)	3	3-1/2 x 3.260 x .120 (T6)		1.498
MILL ORDER	4	4-1/2 x 4.260 x .120		1.942
MILL ORDER 32-63-311 (NC)	5	5.563 x 5.295 x .134		2.686
MILL ORDER	6	6-5/8 x 6.357 x .134		3.214

## Grip Rail - **NEW!**

Stock Code	Description	Stock Code	Description
GR-12	12" Polished & Anodized	GRM-12	12" Mill Finish
GR-14	14" Polished & Anodized	GRM-14	14" Mill Finish
GR-18	18" Polished & Anodized	GRM-18	18" Mill Finish
GR-24	24" Polished & Anodized	GRM-24	24" Mill Finish
GR-36	36" Polished & Anodized	GRM-36	36" Mill Finish



Grip Rails

Items marked as MILL ORDER are non stock but available.  
 Product codes listed on MILL ORDER items are for die reference only.  
 Customer must specify length, alloy & temper.

Standards 24



**Eastern Metal Supply**  
 Quality Shapes In Aluminum

**EMS FL**  
 1-800-432-2204

(561) 588-4780 - fax

**EMS NC/DE/GA**  
 1-800-343-8154

(704) 391-2267 - fax

**EMS TX/AR**  
 1-800-996-6061

(281) 656-2297 - fax

**EMS MO/OH**  
 1-888-822-6061

(314) 344-3349 - fax

Additional Locations: West Palm Beach & Lakeland, FL; Newark, DE; Akron, OH, Van Buren, AR; Atlanta, GA and Dallas, TX

website: [www.EasternMetal.com](http://www.EasternMetal.com)

e-mail: [info@EasternMetal.com](mailto:info@EasternMetal.com)

version: 06/02/20



### SCH 40 Aluminum Pipe End Caps

#### Mill Finish

APC-100-MF	1
APC-125-MF	1-1/4
APC-150-MF	1-1/2
APC-200-MF	2

#### Anodized

APC-750	3/4
APC-100	1
APC-125	1-1/4
APC-150	1-1/2
APC-200	2

### SCH 40 Flat End Caps

FEC-100-MF	1" (Mill Finish)
------------	------------------



### SCH 40 Black Plastic End Caps

RN1DBK1	3/4"
RN1-1/4DBK1	1"
RN1625DBK1	1-1/4"

